

## TYPICAL APPLICATION



## PRODUCT DESCRIPTION

menzolit<sup>®</sup> BMC 1100 is a bulk moulding compound based on unsaturated polyester resin. The product is glass fibre reinforced and contains mineral fillers. In case of fire the product doesn't melt, neither does it form droplets nor is smoke generation excessive. The material is compression moulded in heated steel moulds. It is recommended to work with chrome plated tools. It does not contain any halogens nor any candidates from the REACH SVHC list.

## PRODUCT SPECIFICATION

High strength material with tough matrix resins, for compression moulding only.

## TYPICAL PROPERTIES

	<b>Standard</b>	<b>Units</b>	
Density	ISO 1183	g/cm <sup>3</sup>	1,8
Shrinkage	ISO 2577	%	0,05
Heat Distortion Temp.	EN ISO 75-2	°C	>200
Continuous Service Temp.	Menzolit	°C	170
Young's Modulus	EN ISO 527-4	GPa	13
Tensile Strength	EN ISO 527-4	MPa	40
Flexural Strength	EN ISO 14125	MPa	130
Flex Modulus	EN ISO 14125	GPa	9
Impact Strength	EN ISO 179	kJ/m <sup>2</sup>	35
Glow Wire Index	IEC 60707-3	°C	
Fire Retardancy	UL 94		
Surface Resistivity	IEC 60093	Ohm	10 <sup>12</sup>
Comparative Tracking Index	IEC 60112	Level	CTI600
Water Absorption	ISO 62	%	< 0,3

## FORM of SUPPLY

menzolit<sup>®</sup> BMC 1100 is packaged in styrene tight bags and placed in cardboard or wooden boxes. Various kinds of packaging available. For alternative packaging please contact our technical service team. Available in limited colours.